



BURKE TITAN HARD

BURKE TITAN HARD

Burke Titan Hard is a penetrating water-based reactive silicate solution specifically designed for protecting concrete floors against abrasion, dusting and spillage. Titan Hard penetrates deeply creating an integral matrix that won't wear away. Titan Hard imparts a low gloss, satin sheen with use without buffing.

Burke Titan Hard is specifically formulated for use on old or new concrete surfaces to improve hardness and abrasion resistance. Use Titan Hard to dustproof concrete surfaces imparting an easy to maintain low sheen surface. Titan Hard can be used for interior and exterior applications since it allows the concrete to breathe while still resisting penetration of oils and other contaminants.

BENEFITS

- Imparts an integral shine that builds with use and won't scratch, peel or discolour like modified acrylic styrene butadiene, urethanes or epoxies.
- Seals and densifies the concrete surface resisting spills, dirt and chemical attack.
- No surface coating to allow black rubber tyre marks.
- Hardens & dustproofs in one easy step on most floors.
- Safe & easy to use; no mixing, no etching, no expensive equipment.

- Protects concrete from detrimental spalling effects of deicing salts.
- No V.O.C., no harmful fumes or odours.
- Breathable sealer for interior or exterior use.
- Can be used to enhance hardened and dustproofed non-metallic, dry shake floors.

The exact coverage depends upon the porosity of the slab. If the concrete is extremely porous, more than one coat may be necessary.

Titan Hard will develop a low gloss satin finish with use. If desired, a floor buffer will bring out the shine immediately.

Architectural Specifications

Sealer/Dustproofers: A ready-to-use clear silicate sealer shall be applied to the concrete slab in accordance with the manufacturers written instructions. Sealer must be guaranteed for 10 years against dusting. Approved product: Burke by Edoco Titan Hard or approved equivalent.

Important: When using Titan Hard in conjunction with a curing compound, use only Burke by Edoco Res. X, Aqua Resin Cure or Super Bondbreaker. Consult ABS for special procedures for use.

Application

Sealer & Hardener Application:
Coverage:

Hard Trowelled Finish	7.4 - 9.8
Broom or Float Finish	4.9 - 7.4
Rough Slab Finish	3.7 - 6.2
Old Concrete	3.7 - 6.2
Vertical Surface - lamb's wool roller recommended	7.4 - 9.8

FOR FULL TECHNICAL SPECIFICATIONS OR DATA SHEET, PLEASE GIVE US A CALL ON THE PHONE NUMBER LISTED BELOW

**ADVANCED BUILDING
SYSTEMS PTY. LTD.**

Unit 2/22 Violet Street, Revesby NSW 2212
PO Box 113, North Revesby NSW 2212
Phone: (02) 9771 1011 Fax: (02) 9792 1414
Email: mjdavis@tiltbilt.com Web: www.tiltbilt.com